



400V ~ (3F+N)
50 Hz

posizione	0	6	5	4	3	2	1
POTENZA	0 kW	2.6 kW	1.75 kW	1.3 kW	0.45 kW	0.34 kW	0.24 kW

LEGENDA	LEGEND	LEGENDE	LEGENDE
B _{1,2...6}	SELETTORE WAEHLSCHALTER	SELECTEUR SELECTOR	
L _{1,2...6}	SPIA MACCHINA IN TENSIONE MACHINE LIVE WARNING LAMP	MASCHINE UNTER SPANNUNG-LAMPE LAMPE APPAREIL SOUS TENSION	
MO	MORSETTIERA MAIN TERMINAL BOARD	KLEMMENBRETT BOITE DE CONNECTION	
R _{1,2...6}	RESISTENZE HEATERS	HEIZUNGEN RESISTANCES	
288106 286106			11 - 11 - 08

COLLEGARE IL CAVO DI ALIMENTAZIONE AD UN SEZIONATORE A PARETE - RELIER LE CABLE D'ALIMENTATION A UN INTERRUPTEUR MURAL - CONNECT THE POWER-SUPPLY CABLE WITH A WALL DISCONNECTOR - BAUSEITS IST EIN HAUPTSCHALTER ZU INSTALLIEREN



6 Platten Elektroherd
6 Platten Elektroherd mit offenem Unterbau
Artikel-Nr.: 288.106/286.106

Schaltplan
15.05.2009